## **BUCKINGHAM MFG.**


## **INSTRUCTIONS FOR MODEL 35033 FOOTPLATE**

The Buckingham footplate attaches to most steel climbers with ease.

Each footplate is specially designed to fit the left and right climber.

Each footplate consists of a top and bottom plate, two star washers, and two fasteners.

ASSEMBLE FOOTPLATE to climber as follows:



- Remove the bottom plate from the complete footplate assembly by removing the two screws
- Match the climbers (left and right) to the corresponding footplate.
- Place the climber stirrup into the slot in the top plate.
- Align the bottom plate holes to the top plate holes and insert the two screws making sure the star washers are between the screw head and bottom plate.
- The plates are designed to swivel slightly on the climber stirrup to allow for ease of movement when working aloft on the pole.

## <u>CAUTIONS</u>:

The rubber sole is **not** intended for dielectric protection, but to prevent the metal bottom from sliding on stone and ice.

The footplate is <u>not</u> designed for walking. OSHA states "climbers are to be removed when going from pole to pole".

**DO NOT USE** footplate with aluminum climbers.

Climbers must be inspected daily for wear due to abrasion from footplate movement.

**NOTE:** Ensure proper fit of product before use. This product <u>can not</u> be returned unless it is in new / unused condition.

BUCKINGHAM MFG. CO. BINGHAMTON, NY www.buckinghammfg.com 1-800-937-2825