

## UPLIFT BLOCK

- Used for uplift conditions
- High-strength aluminum alloy frame
- Side gate locks closed with a spring plunger

### AVAILABLE SHEAVES:



Aluminum



Ductile Iron



Urethane Lined



PART #	SHEAVE	SHEAVE WIDTH	SHEAVE DIAMETER	FRAME OPENING	MAX CABLE DIAMETER	WLL	WEIGHT
DNCB-77	Aluminum	3"	7"	2-1/4"	2-1/4"	2,500 lbs.	15.5 lbs.
DNCB-77DI	Ductile Iron	3"	7"	2-1/4"	2-1/4"	2,500 lbs.	25 lbs.
DNCB-77LS	Urethane Lined	3"	7"	2"	2"	2,500 lbs.	16.5 lbs.

## UPLIFT/HOLD DOWN BLOCK

- High-strength cast iron frame
- Holds down the pulling line or conductor in order to combat the cable from rising out of the stringing block groove
- Can be used to lower conductor for inspection or other work
- Tandem position to reduce conductor stress
- Safety Factor: 5:1



PART #	SHEAVE	SHEAVE WIDTH	SHEAVE DIAMETER	MAX CABLE DIAMETER	WLL	WEIGHT
DNUL-7L	Urethane Lined	3"	7"	2"	3,500 lbs.	25.5 lbs.